Technical Documentation of (EU) No 617/2013

Product type	Notebook	computer
Product category	Α	В
Manufacturer name, address	Acer Italy s.r.l,	
	Via Lepetit, 40, 20020 Lain	ate (MI) Italy
Product model number	Aspire E5-432	Aspire E5-432G
Year of manufacture	20	15
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	37.6 kWh/year	49.6 kWh/year
are disabled (from 1 July 2014)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	Not applicable	61.6 kWh/year
are enabled (from 1 July 2014)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	28.6 kWh/year	37.6 kWh/year
are disabled (from 1 January 2016)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	Not applicable	49.6 kWh/year
are enabled (from 1 January 2016)		
Whether all discrete graphics card are	Not applicable	No
enabled during the test	Trot applicable	140
Whether switchable graphics mode with	Not applicable	Yes
UMA is driving the display during the test	Trot applicable	100
E _{TEC} of highest power-demanding	12.99 kWh/year	22.11 kWh/year
configuration	12.00 KVVIII year	ZZ.11 KVVII/yCai
Idle state power demand	4.51 Watt	7.98 Watt
Sleep mode power demand	0.36 Watt	0.4 Watt
Sleep mode with WOL enabled power	0.4 Watt	0.4 Watt
demand	O. I VVall	0.1 Watt
Off mode power demand	0.15 Watt	0.15 Watt
Off mode with WOL enabled power	0.15 Watt	0.15 Watt
demand		
Maximum power demand	Not applicable	Not applicable
Internal power supply (IPS) efficiency at		
10 %, 20 %, 50 % and 100 % of rated	Not applicable	Not applicable
output power		
External power supply's (EPS) average	87.50%	87.50%
active efficiency		
Noise levels (the declared A-weighted	3.1 B	3.1 B
sound power level, L _{WAd}) of idle mode		
Noise levels (the declared A-weighted	_	
sound power level, L _{WAd}) of "HDD random	3.3 B	3.3 B
seek" mode		
Minimum number of loading cycles that	400 cycles	400 cycles
the batteries can withstand		111 1,0.00

Configuration of memory	2~ 8 GB	2~ 8 GB
Configuration of internal storage	1 piece	1 piece
Configuration of discrete television tuner	0 piece	0 piece
Configuration of discrete audio card	0 piece	0 piece
Configuration of discrete graphics cards	0 piece	1 piece
Configuration of discrete graphics cards	Not applicable	G1
category	Trot approacts	
The external package of the notebook		
provides the information, "The battery in	Yes	Yes
this product cannot be easily replaced by	165	165
users themselves."		
For products with an integrated display,	0	0
the total content of mercury is	0 mg	0 mg
Measurement methodology for E _{TEC}	COMMISSION REGULATI 26 June 2013 implementin the European Parliament a regard to ecodesign requir computer servers: ANNEX II Ecodesign requir 1.3.1. E _{TEC} formula.	g Directive 2009/125/EC of and of the Council with ements for computers and
Measurement methodology for idle mode	EN 62623:2013 — Desktor — Measurement of energy 5.2. Test setup; 5.3.4. Measuring long idle 5.7. True RMS watt meter 5.8. True RMS watt meter Annex E.2 (informative) EN compliant testing methodo	mode; specification; accuracy; NERGY STAR [®] V5
Measurement methodology for sleep mode	EN 62623:2013 — Desktor — Measurement of energy 5.2. Test setup; 5.3.3. Measuring sleep mo 5.4. Test conditions; 5.7. True RMS watt meter 5.8. True RMS watt meter	consumption: ode; specification;

	<u> </u>
Measurement methodology for off mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.
Measurement methodology for IPS efficiency	Not applicable
Measurement methodology for EPS efficiency	EN 50563:2011 External a.c.—d.c. and a.c.—a.c. power supplies — Determination of no-load power and average efficiency of active modes.
Measurement methodology for noise level	ECMA-109 2 nd edition (December 1987) Declared Noise Emission Values of Computer and Business Equipment: 4. Determination of the declared noise emission values. ECMA-74 11 th edition (December 2010) Measurement of Airborne Noise emitted by Information Technology and Telecommunications Equipment: 5. Installation and operating instructions; 6. Method for determination of sound power levels of equipment in reverberation test rooms; 7. Method for determination of sound power levels of equipment under essentially free-field conditions over a reflecting plane; Annex C.15 Equipment category: personal computers and workstations.
Measurement methodology for battery loading cycles	EN 61960:2011 Secondary cells and batteries containing alkaline or other non-acid electrolytes — Secondary lithium cells and batteries for portable applications: 7.6.1 General; 7.6.3 Endurance in cycles (accelerated test procedure).

Sequence of steps for achieving a stable condition with respect to power demand	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.3.3. Measuring sleep mode; 5.3.4. Measuring long idle mode.
Description of how sleep mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode.
Description of how off mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode.
Sequence of events required to reach the mode where the equipment automatically changes to sleep mode	ENERGY STAR® Program Requirements Product Specification for Computers, Eligibility Criteria Version 6.0, Rev. Oct-2013: 1.D.4 Sleep Mode.
Sequence of events required to reach the mode where the equipment automatically changes to off mode	Not applicable
The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode	30 minutes
The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode	30 minutes
The length of time before the display sleep mode is set to activate after user inactivity	10 minutes

User information on the energy-saving potential of power management functionality	http://www.energystar.gov/index.cfm?c=power_mgt.p r_power_mgt_users
User information on how to enable the power management functionality	http://www.energystar.gov/index.cfm?c=power_mgt.p r_power_mgt_users
Test parameter for ambient temperature	25 ℃
Test parameter for test voltage	230 V
Test parameter for frequency	50 Hz
Test parameter for total harmonic	3 %
distortion of the electricity supply system	3 /6
Test parameter for information and	
documentation on the instrumentation,	AC Power Source EXTECH 6800 SERIES
set-up and circuits used for electrical	Power Meter YOKOGAWA WT210
testing	