

Technical Documentation of (EC) No 1275/2008

Product type	Projector
Manufacturer name, address	Acer Italy s.r.l, Via Lepetit, 40, 20020 Lainate (MI) Italy
Product model number	P1385WB, P1285B
Year of manufacture	2015
Standby mode power consumption	0.29 Watt
Off mode power consumption	Not applicable
Networked standby mode power consumption	2.83 Watt
Power consumption of the product in networked standby if all wired network ports are connected and all wireless network ports are activated	Not applicable
For products with an display or light source, the total content of mercury is	17.5 mg
The default time after which the power management function, or similar function, has switched the equipment into standby mode	120 minutes
The default time after which the power management function, or similar function, has switched the equipment into off mode	Not applicable
The default time after which the power management function, or similar function, has switched the equipment into another condition which does not exceed the applicable power consumption requirements for off mode and/or standby mode when the equipment is connected to the mains power source.	120 minutes
The default time after which the power management function, or similar function, has switched the equipment into networked standby mode	15 minutes
Technical justification that the requirements set out in points 2(c) and/or 2(d) and/or 3(b), are inappropriate for the intended use of equipment	Not applicable
Measurement methodology for standby	EN 50564:2011/IEC 62301:2011
Measurement methodology for off mode	EN 50564:2011/IEC 62301:2011

Measurement methodology for networked standby mode	EN 50564:2011/IEC 62301:2011
Description of how standby mode was selected or programmed	The equipment is connected to the mains power source without no wake up power key of projector and LED indicative lamp show red light.
Description of how off mode was selected or programmed	Not applicable
Sequence of steps for achieving a stable condition with respect to power demand	Power measurement result averaged from 600 reading result per 1 sec. within 10 minutes, compliance with specification limit are evaluated using exact values without any benefit from further rounding.
Sequence of events leading to the condition where the equipment automatically changes to standby mode	The projector into Sleep mode by receiving a signal from computer, and also can be wake up from sleep mode by receiving a signal from computer.
Sequence of events leading to the condition where the equipment automatically changes to off mode	Not applicable
Sequence of events leading to the condition where the equipment automatically changes to networked standby mode	The projector into networked standby mode by receiving a signal from computer and lan , and also can be wake up from networked standby mode by receiving a signal from computer.
Notes regarding the operation of the equipment	Not applicable
Guidence on how to activate and deactivate wireless network ports	Not applicable
Test parameter for ambient temperature	22 °C
Test parameter for test voltage	230 V
Test parameter for frequency	50 Hz
Test parameter for total harmonic distortion of the electricity supply system	3 %
Test parameter for information and documentation on the instrumentation, set-up and circuits used for electrical testing	