Technical Documentation of (EU) No 617/2013

Product type	Notebook computer
Product category	A
	Acer Italy s.r.l,
Manufacturer name, address	Viale De Gasperi 88/A
,	20017 Mazzo di Rho (MI) Italy
	Aspire ES1-523;
Product model number	Aspire ES1-524.
Year of manufacture	2016
E _{TEC} allowance with capability	
adjustments when discrete graphics cards	31.8 kWh/year
are disabled (from 1 January 2016)	01.0 KVVIII/year
are disabled (norm 1 baridary 2010)	
E _{TEC} allowance with capability	
adjustments when discrete graphics cards	Not applicable
are enabled (from 1 January 2016)	
Whether all discrete graphics card are	Not applicable
enabled during the test	Not applicable
Whether switchable graphics mode with	Not applicable
UMA is driving the display during the test	Tvot applicable
E _{TEC} of highest power-demanding	17.80 kWh/year
configuration	·
Idle state power demand	6.17 Watt
Sleep mode power demand	0.48 Watt
Sleep mode with WOL enabled power	0.49 Watt
demand Off made naver demand	0.22 \\/a4
Off mode power demand Off mode with WOL enabled power	0.22 Watt
demand	0.22 Watt
Maximum power demand	Not applicable
Internal power supply (IPS) efficiency at	
10 %, 20 %, 50 % and 100 % of rated	Not applicable
output power	
External power supply's (EPS) average	87.80%
active efficiency	07.00%
Noise levels (the declared A-weighted	2.8 B
sound power level, L _{WAd}) of idle mode	2.0 D
Noise levels (the declared A-weighted	
sound power level, L _{WAd}) of "HDD random	2.9 B
seek" mode	

Minimum number of loading cycles that	100
the batteries can withstand	400 cycles
Configuration of memory	2~ 16 GB
Configuration of internal storage	1 piece
Configuration of discrete television tuner	0 piece
Configuration of discrete audio card	0 piece
Configuration of discrete graphics cards	0 piece
Configuration of discrete graphics cards category	Not applicable
The external package of the notebook	
provides the information, "The battery in this product cannot be easily replaced by users themselves."	Yes
For products with an integrated display,	0 mg
the total content of mercury is	
Measurement methodology for E _{TEC}	COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers: ANNEX II Ecodesign requirements and timetable: 1.3.1. E _{TEC} formula.
Measurement methodology for idle mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.4. Measuring long idle mode; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy; Annex E.2 (informative) ENERGY STAR® V5 compliant testing methodology.

Measurement methodology for sleep mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.
Measurement methodology for off mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.
Measurement methodology for IPS efficiency	Not applicable
Measurement methodology for EPS efficiency	EN 50563:2011 External a.c.—d.c. and a.c.—a.c. power supplies — Determination of no-load power and average efficiency of active modes.

	1
Measurement methodology for noise level	ECMA-109 2nd edition (December 1987) Declared Noise Emission Values of Computer and Business Equipment: 4. Determination of the declared noise emission values. ECMA-74 11th edition (December 2010) Measurement of Airborne Noise emitted by Information Technology and Telecommunications Equipment: 5. Installation and operating instructions; 6. Method for determination of sound power levels of equipment in reverberation test rooms; 7. Method for determination of sound power levels of equipment under essentially free-field conditions over a reflecting plane; Annex C.15 Equipment category: personal computers and workstations.
Measurement methodology for battery loading cycles	EN 61960:2011 Secondary cells and batteries containing alkaline or other non-acid electrolytes — Secondary lithium cells and batteries for portable applications: 7.6.1 General; 7.6.3 Endurance in cycles (accelerated test procedure).
Sequence of steps for achieving a stable condition with respect to power demand	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.3.3. Measuring sleep mode; 5.3.4. Measuring long idle mode.
Description of how sleep mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode.

Description of how off mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode.
Sequence of events required to reach the mode where the equipment automatically changes to sleep mode	ENERGY STAR® Program Requirements Product Specification for Computers, Eligibility Criteria Version 6.0, Rev. Oct-2013: 1.D.4 Sleep Mode.
Sequence of events required to reach the mode where the equipment automatically changes to off mode	Not applicable
The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode	30 minutes
The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode	30 minutes
The length of time before the display sleep mode is set to activate after user inactivity	10 minutes
User information on the energy-saving potential of power management functionality	http://www.energystar.gov/index.cfm?c=p ower mgt.pr power mgt users
User information on how to enable the power management functionality	http://www.energystar.gov/index.cfm?c=p ower mgt.pr power mgt users
Test parameter for ambient temperature	25 ℃
Test parameter for test voltage	230 V
Test parameter for frequency	50 Hz
Test parameter for total harmonic	3 %
distortion of the electricity supply system	

Test parameter for information and	Digital Power Meter / YOKOGAWA
documentation on the instrumentation,	WT210
set-up and circuits used for electrical	PROGRAMMABLE AC SOURCE /
testing	CHROMA 61602