Technical Documentation of (EU) No 617/2013

Product type	Integrated desktop computer
Product category	D
Manufacturer name, address	Acer Italy s.r.l,
iviandiacturer frame, address	Via Lepetit, 40, 20020 Lainate (MI) Italy
Product model number	Veriton Z4820;
	Veriton Z6820.
Year of manufacture	2015
E _{TEC} allowance with capability	
adjustments when discrete graphics cards	248 kWh/year
are disabled (from 1 July 2014)	
E _{TEC} allowance with capability	
adjustments when discrete graphics cards	282 kWh/year
are enabled (from 1 July 2014)	
E _{TEC} allowance with capability	
adjustments when discrete graphics cards	187 kWh/year
are disabled (from 1 January 2016)	
E _{TEC} allowance with capability	
adjustments when discrete graphics cards	205 kWh/year
are enabled (from 1 January 2016)	
Whether all discrete graphics card are	Yes
enabled during the test	Tes
Whether switchable graphics mode with	No
UMA is driving the display during the test	INO
E _{TEC} of highest power-demanding	96.60 kWh/year
configuration	30.00 KWII/yeai
Idle state power demand	25.64 Watt
Sleep mode power demand	1.68 Watt
Sleep mode with WOL enabled power	1.68 Watt
demand	
Off mode power demand	0.45 Watt
Off mode with WOL enabled power	1.25 Watt
demand	20
Maximum power demand	Not applicable
Internal power supply (IPS) efficiency at	
10 %, 20 %, 50 % and 100 % of rated	Not applicable
output power	
External power supply's (EPS) average	89.00%
active efficiency	
Noise levels (the declared A-weighted	3.47 B
sound power level, L _{WAd}) of idle mode	
Noise levels (the declared A-weighted	
sound power level, L _{WAd}) of "HDD random	3.44 B
seek" mode	

Minimum number of loading cycles that	Not applicable
the batteries can withstand Configuration of memory	4~16G
Configuration of internal storage	1~2 piece
Configuration of discrete television tuner	0~1 piece
Configuration of discrete audio card	0 piece
Configuration of discrete graphics cards	0~1 piece
Configuration of discrete graphics cards	·
category	G1
The external package of the notebook	
provides the information, "The battery in	
this product cannot be easily replaced by	Not applicable
users themselves."	
For products with an integrated display,	
the total content of mercury is	0 mg
the total content of mercury is	
Measurement methodology for E _{TEC}	COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers: ANNEX II Ecodesign requirements and timetable: 1.1.1. E_{TEC} formula.
Measurement methodology for idle mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.4. Measuring long idle mode; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy; Annex E.2 (informative) ENERGY STAR® V5 compliant testing methodology.
Measurement methodology for sleep mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.

Management months adalogue for off monds	EN 62623:2013 — Desktop and notebook
	computers — Measurement of energy consumption:
	5.2. Test setup;5.3.2. Measuring off mode;
Measurement methodology for off mode	5.4. Test conditions;
	5.7. True RMS watt meter specification;
	5.8. True RMS watt meter accuracy.
	o.o. True rawe watt meter accuracy.
Measurement methodology for IPS	Not applicable
efficiency	
	EN 50563:2011 External a.c.—d.c. and a.c.—a.c.
Measurement methodology for EPS	power supplies — Determination of no-load power
efficiency	and average efficiency of active modes.
	ECMA-109 2nd edition (December 1987) Declared
	Noise Emission Values of Computer and Business
	Equipment:
	4. Determination of the declared noise emission
	values.
	ECMA-74 11th edition (December 2010)
	Measurement of Airborne Noise emitted by
	Information Technology and Telecommunications
Measurement methodology for noise level	Equipment:
	5. Installation and operating instructions;
	6. Method for determination of sound power levels
	of equipment in reverberation test rooms;
	7. Method for determination of sound power levels
	of equipment under essentially free-field conditions
	over a reflecting plane; Annex C.15 Equipment category: personal
	computers and workstations.
Measurement methodology for battery	p. 1. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.
loading cycles	Not applicable
	EN 62623:2013 — Desktop and notebook
	computers — Measurement of energy consumption:
Sequence of steps for achieving a stable	5.2. Test setup;
condition with respect to power demand	5.3.2. Measuring off mode;
	5.3.3. Measuring sleep mode;
	5.3.4. Measuring long idle mode.

	7
Description of how sleep mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode.
Description of how off mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode.
Sequence of events required to reach the mode where the equipment automatically changes to sleep mode	ENERGY STAR® Program Requirements Product Specification for Computers, Eligibility Criteria Version 6.0, Rev. Oct-2013: 1.D.4 Sleep Mode.
Sequence of events required to reach the mode where the equipment automatically changes to off mode	Not applicable
The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode	30 minutes
The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode	30 minutes
The length of time before the display sleep mode is set to activate after user inactivity	10 minutes
User information on the energy-saving potential of power management functionality	http://www.energystar.gov/index.cfm?c=power_mgt. pr_power_mgt_users
User information on how to enable the power management functionality	http://www.energystar.gov/index.cfm?c=power_mgt. pr_power_mgt_users
Test parameter for ambient temperature	25 ℃
Test parameter for test voltage	230 V
Test parameter for frequency	50 Hz

Test parameter for total harmonic		3 %
distortion of the electricity supply system		3 %
Test parameter for information and		
documentation on the instrumentation,	Digital Power Meter- Yokogawa WT210	
set-up and circuits used for electrical	Programmable AC Soure- Chroma 61603	
testing		