## Technical Documentation of (EU) No 617/2013

| Product type   | Notebook computer  |
|--|--|
| Product category   | A  |
| Manufacturer name, address   | Acer Italy s.r.l.<br>Via Lepetit, 40, 20020 Lainate (MI) Italy |
| Product model number   | Chromebook Spin 15 CP315-1H;<br>Chromebook 15 CB315-1H.        |
| Year of manufacture  | 2018   |
| E <sub>TEC</sub> allowance with capability<br>adjustments when discrete graphics cards<br>are disabled (from 1 January 2016) | 28.6 kWh/year  |
| E <sub>TEC</sub> allowance with capability<br>adjustments when discrete graphics cards<br>are enabled (from 1 January 2016)  | Not applicable   |
| Whether all discrete graphics card are<br>enabled during the test  | Not applicable   |
| Whether switchable graphics mode with UMA is driving the display during the test   | Not applicable   |
| E <sub>TEC</sub> of highest power-demanding configuration  | 14.02 kWh/year   |
| Idle state power demand  | 4.67 Watt  |
| Sleep mode power demand  | 0.98 Watt  |
| Sleep mode with WOL enabled power demand   | Not applicable   |
| Off mode power demand  | 0.17 Watt  |
| Off mode with WOL enabled power demand   | Not applicable   |
| Maximum power demand   | Not applicable   |
| Internal power supply (IPS) efficiency at 10 %, 20 %, 50 % and 100 % of rated output power                                   | Not applicable   |
| External power supply's (EPS) average active efficiency  | 88.60%   |
| Noise levels (the declared A-weighted sound power level, L <sub>WAd</sub> ) of idle mode                                     | 2.80 B   |
| Noise levels (the declared A-weighted sound power level, L <sub>WAd</sub> ) of "HDD random seek" mode                        | Not applicable   |

| Minimum number of loading cycles that             | 400 cyclos  |
|---|---|
| the batteries can withstand                       | 400 cycles  |
| Configuration of memory                           | 2~8GB   |
| Configuration of internal storage                 | 1 piece   |
| Configuration of discrete television tuner        | 0 piece   |
| Configuration of discrete audio card              | 0 piece   |
| Configuration of discrete graphics cards          | 0 piece   |
| Configuration of discrete graphics cards category | Not applicable  |
| The external package of the notebook              |   |
| provides the information, "The battery in         |   |
| this product cannot be easily replaced by         | Yes   |
| users themselves."                                |   |
| For products with an integrated display,          |   |
| the total content of mercury is                   | 0 mg  |
| the total content of mercury is                   |   |
| Measurement methodology for E <sub>TEC</sub>      | COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers:  ANNEX II Ecodesign requirements and timetable:  1.3.1. E <sub>TEC</sub> formula. |
| Measurement methodology for idle mode             | EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.4. Measuring long idle mode; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy; Annex E.2 (informative) ENERGY STAR® V5 compliant testing methodology.             |

| Measurement methodology for sleep mode     | EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy. |
|--|--|
| Measurement methodology for off mode       | EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.   |
| Measurement methodology for IPS efficiency | Not applicable   |
| Measurement methodology for EPS efficiency | EN 50563:2011 External a.c.—d.c. and a.c.—a.c. power supplies — Determination of no-load power and average efficiency of active modes.   |

|   | 1  |
|---|--|
| Measurement methodology for noise level   | ECMA-109 2nd edition (December 1987) Declared Noise Emission Values of Computer and Business Equipment: 4. Determination of the declared noise emission values. ECMA-74 11th edition (December 2010) Measurement of Airborne Noise emitted by Information Technology and Telecommunications Equipment: 5. Installation and operating instructions; 6. Method for determination of sound power levels of equipment in reverberation test rooms; 7. Method for determination of sound power levels of equipment under essentially free-field conditions over a reflecting plane; Annex C.15 Equipment category: personal computers and workstations. |
| Measurement methodology for battery loading cycles                              | EN 61960:2011 Secondary cells and batteries containing alkaline or other non-acid electrolytes — Secondary lithium cells and batteries for portable applications: 7.6.1 General; 7.6.3 Endurance in cycles (accelerated test procedure).   |
| Sequence of steps for achieving a stable condition with respect to power demand | EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.3.3. Measuring sleep mode; 5.3.4. Measuring long idle mode.  |
| Description of how sleep mode was selected or programmed                        | EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode.  |

| Description of how off mode was selected or programmed  | EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode.            |
|---|--|
| Sequence of events required to reach the mode where the equipment automatically changes to sleep mode   | ENERGY STAR® Program Requirements Product Specification for Computers, Eligibility Criteria Version 6.0, Rev. Oct-2013:  1.D.4 Sleep Mode. |
| Sequence of events required to reach the mode where the equipment automatically changes to off mode   | Not applicable   |
| The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode | 30 minutes   |
| The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode                       | 30 minutes   |
| The length of time before the display sleep mode is set to activate after user inactivity   | 10 minutes   |
| User information on the energy-saving potential of power management functionality   | http://www.energystar.gov/index.cfm?c=p<br>ower_mgt.pr_power_mgt_users   |
| User information on how to enable the power management functionality  | http://www.energystar.gov/index.cfm?c=p<br>ower mgt.pr power mgt users   |
| Test parameter for ambient temperature  | 25 ℃   |
| Test parameter for test voltage   | 230 V  |
| Test parameter for frequency Test parameter for total harmonic  | 50 Hz  |
| distortion of the electricity supply system   | 3 %  |

Test parameter for information and documentation on the instrumentation, set-up and circuits used for electrical testing

Equipment setup:

1.1 AC Power Source: Chroma model 61602

1.2 Power-Meter: YOKOGAWA WT210

2. Test Condition:

2.1 AC Power Source :

2.1.1 Input power and frequency: 230Volts (+/-1%) AC, 50Hz (+/-1%)

Relative Humidity: 50%