Technical Documentation of (EC) No 1275/2008

Entry	Product type	Notebook
No.		Appriltable a r l
1	Manufacturer name, address	Acer Italy s.r.l, Viale delle Industrie 1/A, 20020 Arese
		(MI), Italy
	Product model number	A314-35;
		A114-33;
2		A314-35S;
		B114-33;
		B314-35S;
		B314-35.
3	Year of manufacture	2021
4	For products with a display unit or light	0 mg
	source, the total content of mercury is	
5	Power consumption of standby mode	Not applicable
6	Power consumption of off mode	Not applicable
	The default time after which the power	
7	management function, or similar function,	Not applicable
	has switched the equipment into standby	
	mode	
	The default time after which the power	
8	management function, or similar function,	720 minutes
	has switched the equipment into off mode	
	The default time after which the power	
	management function, or similar function,	
9	has switched the equipment into another	
	condition which does not exceed the	Not applicable
	applicable power consumption	
	requirements for off mode and/or standby	
	mode when the equipment is connected	
	to the mains power source.	

10	Equipment characteristics relevant for assessing conformity with the requirements set out in point 2(c) and/or 2(d)	Not applicable
11	Technical justification that the requirements set out in points 2(c) and/or 2(d) are inappropriate for the intended use of equipment	Not applicable
12	Measurement methodology for standby mode	Not applicable
13	Measurement methodology for off mode	IEC 62301:2011
14	Description of how standby mode was selected or programmed	Not applicable
15	Description of how off mode was selected or programmed	We follow the test procedure of IEC 62301:201
16	Sequence of steps for achieving a stable condition with respect to power demand	We follow the test procedure of IEC 62301:201
17	Sequence of events leading to the condition where the equipment automatically changes to standby mode	Not applicable
18	Sequence of events leading to the condition where the equipment automatically changes to off mode	We follow the test procedure of IEC 62301:201
19	Notes regarding the operation of the equipment	Not applicable
20	Test parameter for ambient temperature	25 °C
21	Test parameter for test voltage	230 V
22	Test parameter for frequency	50 Hz
23	Test parameter for total harmonic distortion of the electricity supply system	3%

/4	Test parameter for information and documentation on the instrumentation, set-up and circuits used for electrical testing	AC Power Source: Chroma AC Source 61602 Power-Meter: Yokogawa WT 210
----	---	--