Technical Documentation of (EU) No 617/2013

Entry No.	Product type			Desktop o	computer
1	Product category	Α	В	С	D
2	Manufacturer name, address	Acer Italy s.r.l, Viale delle Indu	ustrie 1/A, 2002	20 Arese (MI), Ita	aly
3	Product model number				N50-620
4	Year of manufacture		1	202	21
	E _{TEC} allowance with capability adjustments				
5	when discrete graphics cards are disabled				247 kWh/year
	(from 1 January 2016)				
•	E _{TEC} allowance with capability adjustments				0571144
6	when discrete graphics cards are enabled				357 kWh/year
	(from 1 January 2016)				
7	Whether all discrete graphics card are enabled during the test				Yes
8	Whether switchable graphics mode with				Not applicable
	UMA is driving the display during the test				
9	E _{TEC} of highest power-demanding				150.00 kWh/year
	configuration				
10	Idle state power demand				28.74 Watt
11	Sleep mode power demand				1.45 Watt
12	Sleep mode with WOL enabled power				1.46 Watt
40	demand				0.00 M. ((
13	Off mode power demand				0.93 Watt
14	Off mode with WOL enabled power demand				0.94 Watt
15	Maximum power demand				Not applicable
	Internal power supply (IPS) efficiency at 10				Output Load 100%, Efficiency 89.5% Output Load 50%, Efficiency 92.9%
16	%, 20 %, 50 % and 100 % of rated output				Output Load 20%, Efficiency 92.4%
	power				Output Load 10%, Efficiency 90.0%
17	External power supply's (EPS) average active efficiency				Not applicable
	Noise levels (the declared A-weighted				
18	sound power level, L _{WAd}) of idle mode				3.60 B
19	Noise levels (the declared A-weighted				3.70 B
19	sound power level, L _{WAd}) of "HDD random seek" mode				3.70 B
	Seek IIIoue				
20	Minimum number of loading cycles that the				Not applicable
20	batteries can withstand				пот аррисаше
21	Configuration of memory (unit: GB)				4-64
22	Configuration of internal storage (unit: piece)				1-4
23	Configuration of discrete television tuner (unit: piece)				0
	Configuration of discrete audio card (unit:				
24	piece)				0
25	Configuration of discrete graphics cards				1
	(unit: piece)				<u> </u>

26	Configuration of discrete graphics cards category				G7
27	The external package of the notebook provides the information, "The battery in this product cannot be easily replaced by users themselves."				Ntot appliable
28	For products with an integrated display, the total content of mercury is				Ntot appliable
29	Measurement methodology for E _{TEC}	COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers: ANNEX II Ecodesign requirements and timetable: 1.3.1. ETEC formula.			
30	Measurement methodology for idle mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.4. Measuring long idle mode; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy; Annex E.2 (informative) ENERGY STAR® V5 compliant testing methodology.			
31	Measurement methodology for sleep mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.			
32	Measurement methodology for off mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.			
33	Measurement methodology for IPS efficiency	Not applicable			
34	Measurement methodology for EPS efficiency	EN 50563:2011 External a.c.—d.c. and a.c.—a.c. power supplies — Determination of no-load power and average efficiency of active modes.			

35	Measurement methodology for noise level	ECMA-109 2nd edition (December 1987) Declared Noise Emission Values of Computer and Business Equipment: 4. Determination of the declared noise emission values. ECMA-74 11th edition (December 2010) Measurement of Airborne Noise emitted by Information Technology and Telecommunications Equipment: 5. Installation and operating instructions; 6. Method for determination of sound power levels of equipment in reverberation test rooms; 7. Method for determination of sound power levels of equipment under essentially free-field conditions over a reflecting plane; Annex C.15 Equipment category: personal computers and workstations.
36	Measurement methodology for battery loading cycles	EN 61960:2011 Secondary cells and batteries containing alkaline or other non-acid electrolytes — Secondary lithium cells and batteries for portable applications: 7.6.1 General; 7.6.3 Endurance in cycles (accelerated test procedure).
37	Sequence of steps for achieving a stable condition with respect to power demand	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.3.3. Measuring sleep mode; 5.3.4. Measuring long idle mode.
38	Description of how sleep mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode.
39	Description of how off mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode.
40	Sequence of events required to reach the mode where the equipment automatically changes to sleep mode	ENERGY STAR® Program Requirements Product Specification for Computers, Eligibility Criteria Version 6.0, Rev. Oct-2013: 1.D.4 Sleep Mode.
41	Sequence of events required to reach the mode where the equipment automatically changes to off mode	Not applicable
42	The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode	30 minutes
43	The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode	30 minutes
44	The length of time before the display sleep mode is set to activate after user inactivity	10 minutes

45	User information on the energy-saving potential of power management functionality	http://www.energystar.gov/index.cfm?c=power_mgt.pr_power_mgt_users
46	User information on how to enable the power management functionality	http://www.energystar.gov/index.cfm?c=power_mgt.pr_power_mgt_users
47	Test parameter for ambient temperature	25 ℃
48	Test parameter for test voltage	230 V
49	Test parameter for frequency	50 Hz
50	Test parameter for total harmonic distortion of the electricity supply system	3%
51	Test parameter for information and documentation on the instrumentation, set- up and circuits used for electrical testing	EXTECH AC Power source 6900 Chroma digital power meter 66202