



Barcode
MC.XXXXX.XXX



HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE



P/N: 4J.3TU01.001

SPECIFICATIONS

Projection system	DLP™
Resolution	<ul style="list-style-type: none"> H6530BD/E352D/HE-823J/GM522/VH-422: Native: 1080p (1920 x 1080) Maximum: WUXGA (1920 x 1200) (supports reduce blanking only) P1650/M366/PE-WU46/PR620/MF-520/X1626H/D566D/EV-WU57H/ P1625/M446/DX625/BS-525: Native: WUXGA (1920 x 1200) Maximum: WUXGA (1920 x 1200) (supports reduce blanking only)
Computer compatibility	<p>IBM PC and compatibles, Apple Macintosh, iMac and VESA standards: VGA, SVGA, XGA, SXGA, SXGA+, WXGA, WXGA+, WSXGA+, HD720, HD1080, WUXGA (VGA source)</p> <p>IBM PC and compatibles, Apple Macintosh, iMac and VESA standards: VGA, SVGA, XGA, SXGA, SXGA+, WXGA, WXGA+, WSXGA+, HD720, HD1080, WUXGA (HDMI source)</p>
Video compatibility	NTSC (3.58/4.43), PAL (M/N), PAL 60, SECAM, HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect ratio	Auto, 4:3, 16:9, Full, L.Box
Displayable colors	1.07 billion colors
Projection lens	<ul style="list-style-type: none"> H6530BD/E352D/HE-823J/GM522/VH-422: F = 2 – 2.05, f = 15.85 mm – 17.44 mm, 1:1.1 Manual Zoom and Manual Focus P1650/M366/PE-WU46/PR620/MF-520/X1626H/D566D/EV-WU57H/ P1625/M446/DX625/BS-525: F = 1.94 – 2.06, f = 15.57 mm – 18.67 mm, 1:1.2 Manual Zoom and Manual Focus
Projection screen size (diagonal)	<ul style="list-style-type: none"> H6530BD/E352D/HE-823J/GM522/VH-422: 27" – 301" (68.6 cm – 764.5 cm) P1650/M366/PE-WU46/PR620/MF-520/X1626H/D566D/EV-WU57H/ P1625/M446/DX625/BS-525: 26" – 290" (66 cm – 736.6 cm)
Projection distance with clear focus	1 m – 11 m
Throw ratio	<ul style="list-style-type: none"> H6530BD/E352D/HE-823J/GM522/VH-422: 1.50 – 1.65 (100" ± 3% @ 3.23 m) P1650/M366/PE-WU46/PR620/MF-520/X1626H/D566D/EV-WU57H/ P1625/M446/DX625/BS-525: 1.47 – 1.76 (63" ± 3% @ 2 m)
Horizontal scan rate	31 – 135 KHz
Vertical refresh scan rate	48 – 120 Hz
Keystone correction	+/-40 Degrees (Vertical), Manual & Auto
Digital zoom	0.8 – 2 X

Audio	<ul style="list-style-type: none"> X1626H/D566D/EV-WU57H/P1625/M446/DX625/BS-525/H6530BD/ E352D/HE-823J/GM522/VH-422: 3W speaker x 1 P1650/M366/PE-WU46/PR620/MF-520: 10W speaker x 1 				
Weight	Approximate 3.5 kg (7.72 lbs.)				
Dimensions (W x D x H)	343 x 258 x 112 mm (11.8" x 8.7" x 3.6") 343 x 258 x 124.6 mm (11.8" x 8.7" x 4.1") (with tilt adjusting wheels)				
Power supply	Universal AC input 100 - 240 V, input frequency 50/60 Hz				
Power consumption	<ul style="list-style-type: none"> H6530BD/E352D/HE-823J/GM522/VH-422/P1650/M366/PE-WU46/ PR620/MF-520: Standard mode: 260 W @100 VAC ECO mode: 220 W @ 100 VAC Standby mode: < 0.5 W X1626H/D566D/EV-WU57H/P1625/M446/DX625/BS-525: Standard mode: 310 W @100 VAC ECO mode: 240 W @ 100 VAC Standby mode: < 0.5 W 				
Operating temperature	0°C to 40°C / 32°F to 104°F				
I/O connectors	<table border="0"> <tr> <td>H6530BD/E352D/HE-823J/GM522/ VH-422:</td> <td>P1650/M366/PE-WU46/PR620/MF- 520/X1626H/D566D/EV-WU57H/ P1625/M446/DX625/BS-525:</td> </tr> <tr> <td> <ul style="list-style-type: none"> Power socket x 1 USB Type A (DC 5V OUT) x 1 VGA input x 1 VGA output x 1 RS232 x 1 3.5 mm audio jack input x 1 3.5 mm audio jack output x 1 Composite video x 1 HDMI x 1 </td> <td> <ul style="list-style-type: none"> Power socket x 1 USB Type A (DC 5V OUT) x 1 VGA input x 2 VGA output x 1 RS232 x 1 3.5 mm audio jack input x 1 3.5 mm audio jack output x 1 Composite video x 1 HDMI/MHL x 1 HDMI x 1 </td> </tr> </table>	H6530BD/E352D/HE-823J/GM522/ VH-422:	P1650/M366/PE-WU46/PR620/MF- 520/X1626H/D566D/EV-WU57H/ P1625/M446/DX625/BS-525:	<ul style="list-style-type: none"> Power socket x 1 USB Type A (DC 5V OUT) x 1 VGA input x 1 VGA output x 1 RS232 x 1 3.5 mm audio jack input x 1 3.5 mm audio jack output x 1 Composite video x 1 HDMI x 1 	<ul style="list-style-type: none"> Power socket x 1 USB Type A (DC 5V OUT) x 1 VGA input x 2 VGA output x 1 RS232 x 1 3.5 mm audio jack input x 1 3.5 mm audio jack output x 1 Composite video x 1 HDMI/MHL x 1 HDMI x 1
H6530BD/E352D/HE-823J/GM522/ VH-422:	P1650/M366/PE-WU46/PR620/MF- 520/X1626H/D566D/EV-WU57H/ P1625/M446/DX625/BS-525:				
<ul style="list-style-type: none"> Power socket x 1 USB Type A (DC 5V OUT) x 1 VGA input x 1 VGA output x 1 RS232 x 1 3.5 mm audio jack input x 1 3.5 mm audio jack output x 1 Composite video x 1 HDMI x 1 	<ul style="list-style-type: none"> Power socket x 1 USB Type A (DC 5V OUT) x 1 VGA input x 2 VGA output x 1 RS232 x 1 3.5 mm audio jack input x 1 3.5 mm audio jack output x 1 Composite video x 1 HDMI/MHL x 1 HDMI x 1 				

Note:

- The specifications listed above are subject to change without notice.
- For final specifications, please refer to Acer's published marketing specifications.
- Find manuals and other documents for your Acer product on the official Acer support website.



Scan to get user's manual.