



Lithium-ion Rechargeable Battery Pack

LG Chem, Ltd.

PSDS for Acer Batteries.

The Attached MSDS, accurately represents the chemical construction, of the Acer Batteries listed below.

No.	Acer Model Name	Capacity	List
1	AS16A8K	42Wh	INR18650C4
2	AS16B8J	61Wh	INR18650C4
3	AC14B8K	48Wh	ICP485780A1
4	AC14A8L	52Wh	ICP666180A1
5	AP14F8K	34.5Wh	ICP30100107L1
6	AC16A8N	69Wh	ICP666180B12
7	AP16J8K	45Wh	ICP595490L1
8	AC14B18J	36.7Wh	ICP485780B2
9	AC16B8K	48Wh	ICP485780A1
10	AC14B8K	48Wh	ICP485780A1
11	AC14B18J	36Wh	ICP485780B2
12	AC15A8J	38Wh	R485780C3
13	AC17A8M	61.9Wh	ICP666180B1
14	AC17B8K	48Wh	ICP485780A1
15	AP18B18J	34.31Wh	ICP575577B1
16	AP14A8M	22Wh	ICP3657101L1
17	AP16L8J	36.5Wh	ICP359190D1

Signed by Representative: 

Jin Soo Park
Vice chairman&CEO
LG Chem.Ltd.

129 Yeouil-daero, Yeonodeunpo-gu, Seoul 150-721, Korea

18	AP18H18J	34.31Wh	ICP575577B1
19	AP18H8L	51.47Wh	ICP575577B1
20	AP18C8K	50.29Wh	P498170A1
21	AP18E8M	57.48Wh	MCP367088A1

Signed by Representative:



SAFETY DATA SHEET

Lithium-Ion Battery

LG Chem, Ltd.

1. Chemical Product and Company Identification

Product Identification

Lithium-Ion Battery (All models manufactured by LG Chem, Ltd)

Manufacturer

LG Chem, Ltd.

LG Twin Towers, 128, Yeoui-daero,

Yeongdeungpo-gu, Seoul 150-721, Korea

Emergency Telephone Number

82-2-3773-7256

2. Composition Information

Hazardous Ingredients	%	CAS Number
Aluminum Foil	2-10	7429-90-5
Nickel compound (proprietary)	0-25	
Manganese compound (proprietary)	0-15	
Cobalt compound (proprietary)	4-50	
Styrene-Butadiene-Rubber	<1	
Polyvinylidene Fluoride (PVDF)	<5	24937-79-9
Copper Foil	2-10	7440-50-8
Carbon (proprietary)	10-30	7440-44-0
Electrolyte (proprietary)	10-20	
Stainless steel, Nickel and inert materials	Remainder	N/A

3. Hazards Identification

Emergency Overview

May explode in a fire, which could release hydrogen fluoride gas.

Use extinguishing media suitable for materials burning in fire.

Primary routes of entry

Skin contact	:	NO
Skin absorption	:	NO
Eye contact	:	NO
Inhalation	:	NO
Ingestion	:	NO

Symptoms of exposure

Skin contact

No effect under routine handling and use.

Skin absorption

No effect under routine handling and use.

Eye contact

No effect under routine handling and use.

Inhalation

No effect under routine handling and use.

Reported as carcinogen

Not applicable

4. First Aid Measures

Inhalation

Not a health hazard.

Eye contact

Not a health hazard.

Skin contact

Not a health hazard.

Ingestion

If swallowed, obtain medical attention immediately.

IF EXPOSURE TO INTERNAL MATERIALS WITHIN CELL DUE TO DAMAGED OUTER CASING, THE FOLLOWING ACTIONS ARE RECOMMENDED ;

Inhalation

Leave area immediately and seek medical attention.

Eye contact

Rinse eyes with water for 15 minutes and seek medical attention.

Skin contact

Wash area thoroughly with soap and water and seek medical attention.

Ingestion

Drink milk/water and induce vomiting; seek medical attention.

5. Fire Fighting Measures

General Hazard

Cell is not flammable but internal organic material will burn if the cell is incinerated. Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

Extinguishing Media

Use extinguishing media suitable for the materials that are burning.

Special Firefighting Instructions

If possible, remove cell(s) from fire fighting area. If heated above 125°C, cell(s) may explode/vent.

Firefighting Equipment

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

6. Accidental Release Measures

On Land

Place material into suitable containers and call local fire/police department.

In Water

If possible, remove from water and call local fire/police department.

7. Handling and Storage

Handling

No special protective clothing required for handling individual cells.

Storage

Store in a cool, dry place.

8. Exposure Controls / Personal Protection**Engineering controls**

Keep away from heat and open flame. Store in a cool dry place.

Personal ProtectionRespirator

Not required during normal operations. SCBA required in the event of a fire.

Eye/face protection

Not required beyond safety practices of employer.

Gloves

Not required for handling of cells.

Foot protection

Steel toed shoes recommended for large container handling.

9. Physical and Chemical Properties

State	Solid
Odor	N/A
PH	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

10. Stability and Reactivity

Reactivity

None

Incompatibilities

None during normal operation. Avoid exposure to heat, open flame, and corrosives.

Hazardous Decomposition Products

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

Conditions To Avoid

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

11. Toxicological Information

This product does not elicit toxicological properties during routine handling and use.

Sensitization	Teratogenicity	Reproductive toxicity	Acute toxicity
NO	NO	NO	NO

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

12. Ecological Information

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

13. Disposal Considerations

California regulated debris

RCRA Waste Code : Nonregulated

Dispose of according to all federal, state, and local regulations.

14. Transport Information

Lithium batteries are classified in Class 9 – Miscellaneous dangerous goods as:

- UN 3480, Lithium ion batteries
- UN 3481, Lithium ion batteries contained in equipment; or
- UN 3481, Lithium ion batteries packed with equipment.

With regard to transport of the product, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions,
- The International Air Transport Association (IATA) Dangerous Goods Regulations
- The International Maritime Dangerous Goods (IMDG) Code,
- US Hazardous Materials Regulations 49 CFR (Code of Federal Regulations) Sections 173-185 Lithium batteries and cells,
- The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries,

If those lithium-ion batteries are packed with or contained in an equipment, then it is the responsibility of the shipper to ensure that the consignment are packed in compliance to the latest edition of the IATA Dangerous Goods Regulations Section II of either Packing Instruction

966 or 967 in order for that consignment to be declared as NOT RESTRICTED (non-hazardous/non-Dangerous). If those lithium-ion batteries are packed with or contained in an equipment, UN No. is UN3481

Each cell or battery is of the type proven to meet the requirements of each test in the UN Manual of Tests and Criteria, Part III, subsection 38.3;

The product has been evaluated according to the UN Manual of Tests and Criteria.

No.	Test Item	Criteria	Result
Test 1	Altitude simulation	-No leakage, venting, disassembly, rupture and no fire. -Measuring mass before/after each test. (If M>5g, less than 0.1%) -Measuring voltage before/after each test. (more than 90%)	Pass
Test 2	Thermal test		Pass
Test 3	Vibration		Pass
Test 4	Shock		Pass
Test 5	External circuit short	-No disassembly, rupture and fire within six hours of this test.	Pass
Test 6	Impact	-Max. temperature should not exceed 170°C.	Pass
Test 7	Overcharge	-No disassembly and fire within seven days of the test.	Pass

15. Regulatory Information

This product is not hazardous under the criteria of the Federal Occupational Safety and Health

Administration(OSHA) Hazard Communication Standard.(29 CFR 1910.1200)

IATA Dangerous Goods Regulations 60th Edition Effective 1 January 2019.

☐ Hazardous ☒ Non-hazardous

16. Other Information

The data in this Product Safety Data Sheet relates only to the specific product designated herein and does not relate to use in combination with any other product or in any process. This PSDS may not meet regulatory requirements in other countries. This information is based on technical information believed to be reliable. It is subject to revision as additional knowledge and experiences are gained.

REFERENCE

International Chemical Safety Cards(ICSCs) International Occupational Safety and Health Information Centre(CIS) 0710 March 1999

Opinion of the scientific committee on toxicity, ecotoxicity and the environment(CSTEE)

Adopted by the CSTEE during the 43rd plenary meeting of 28 May 2004

UN-Recommendations on the Transport of Dangerous Goods Model Regulations.
(ST/SG/AC. 10/11 Rev.5/Amend2)

UN regulation

- UN number: 3480 (3481 when the battery is contained in equipment or packed with equipment)

Jin Soo Park
Vice chairman&CEO
LG Chem.Ltd.
128,Yeoui-daero, Yeongdeungpo-gu, Seoul 150-721,Korea