

# Product Safety Data Sheet

## LGC Lithium- Ion Rechargeable Polymer Battery Pack

### LG CHEMICAL LTD

#### SECTION 1 Product and Company Identification

##### PRODUCT IDENTIFICATION

Acer AC14B8K, LGC 1P4S Lithium-Ion Polymer Battery Pack

Revision date: Jan 01, 2014

Battery pack Electric Power Capacity: 48Wh

##### MANUFACTURING/DISTRIBUTOR

LG Chemical Ltd. Twin Tower Youido-Dong 120, Youngdeungpo-Ku, Seoul, Korea

##### PHONE NUMBER

Tel: + 82-2-3773-3739

#### SECTION 2 Composition and Information on Ingredients

Component		%	CAS Number	Remarks
Cases(PC)		9-11	103598-77-2	No dangerous
PCB Assembly	Glass cloth	1-2	65997-17-3	No dangerous
	Copper		7440-50-8	
	Epoxy		26265-8-7	
	2-Butoxy ethyl acetate		112-07-2	
	Dipropylene glycol methyl ether		34590-94-8	
	Acrylate resins		Various	
	Epoxy resin mixture		N/A	
	Dipropylene glycol methyl ether		34590-94-8	
	Acrylate resins		Various	
	Gamma-Butyrolactone		00000096-48-0	
	Other components		N/A	

**LG CHEM  
PRODUCT SAFETY DATA SHEET**

Lithium Ion Cell: **LGC ICP485780A1**

<b>Hazardous Ingredients</b>	<b>%</b>	<b>CAS Number</b>
Aluminum Foil	2-10	7429-90-5
Metal Oxide (proprietary)	20-50	
Polyvinylidene Fluoride (PVDF)	<5	24937-79-9
Copper Foil	2-10	7440-50-8
Carbon (proprietary)	10-30	7440-44-0
Electrolyte (proprietary)	10-20	
Stainless steel, Nickel and inert materials	Remainder	N/A

**\* Watt-hour : 12 Wh**

**UN CLASS**

1. Even classified as lithium batteries (UN3480), 2015 IATA Dangerous Goods Regulations 56<sup>th</sup> edition Packing Instruction 965 section II or IB is applied.

The general and additional requirements apply to all lithium ion cells and batteries prepared for transport according to this packing instruction:

- 1) Section IA applies to lithium ion cells with a Watt-hour rating in excess of 20 Wh and lithium ion batteries with a Watt-hour rating in excess of 100 Wh, or to quantities of lithium ion cells or batteries in excess of those permitted in Section IB of this packing instruction which must be assigned to Class 9 and are subject to all of the applicable requirements of these Regulations;
- 2) Section IB applies to lithium ion cells with a Watt-hour rating not exceeding 20 Wh and lithium ion batteries with a Watt-hour rating not exceeding 100 Wh packed in quantities that exceed the allowance permitted in Section II, Table 965-II; and
- 3) Section II applies to lithium ion cells with a Watt-hour rating not exceeding 20 Wh and lithium ion batteries with a Watt-hour rating not exceeding 100 Wh packed in quantities not exceeding the allowance permitted in Section II, Table 965-II.

**TABLE 965-II**

Contents	Lithium ion cells and/or batteries with a Watt-hour rating of 2.7 Wh or less	Lithium ion cells with a Watt-hour rating of more than 2.7 Wh but not more than 20 Wh	Lithium ion batteries with a Watt-hour rating of more than 2.7 Wh but not more than 100 Wh
1	2	3	4
Maximum number of cells/batteries per package	No limit	8 cells	2 Batteries
Maximum net quantity per package	2.5 kg	N/A	N/A

Cells and/or batteries specified in columns 2, 3 and 4 of Table 965-II must not be combined in the same package.

Each cell or battery is of the type proven to meet the requirements of each test in the UN Manual of Tests and Criteria Part 3 subsection 38.3.

2. Even classified as lithium batteries packed with equipment (UN3481), 2015 IATA Dangerous Goods Regulations 56<sup>nd</sup> edition Packing Instruction 966 section II is applied. The product is handled as Non-Dangerous Goods by meeting the following requirements.

**LG CHEM  
PRODUCT SAFETY DATA SHEET**

Lithium ion cells and batteries offered for transport are not subject to other additional requirements of the UN Regulations if they meet the following.

- . For cells, the Watt-hour rating is not more than 20Wh
- . For batteries, Watt-hour rating is not more than 100Wh

The Watt-hour rating must be marked on outside of the battery case except those manufactured before 1 January, 2009 which may be transported without this marking until 31 December 2012.

- . Each cell or battery is of the type proven to meet the requirements of each test in the UN Manual of Tests and Criteria part (subsection 38.3)
- . Maximum quantity : Minimum needed for the operation of the equipment, plus 2 spares.

And they are out of scope for Special Provision A154 and comply with Special Provision A164.

This product passed 1.2M drop test and comply with UN38.3.

### **SECTION 3 Hazards Identification**

#### **EMERGENCY OVERVIEW**

During a fire, may release irritating gases.

Use extinguishing media suitable for materials burning in fire.

#### **POTENTIAL HEALTH EFFECTS**

##### **EYE**

No effect under routine handling and use.

##### **SKIN**

No effect under routine handling and use. Nothing cause sensitization(allergic reaction)

##### **INHALATION**

No effect under routine handling and use.

#### **CHRONIC EFFECTS**

None known.

#### **CARCINOGENICITY INFORMATION**

The components of this product are not listed by IARC, NTP, OSHA, or ACGH as a carcinogen.

### **SECTION 4 First Aid Measures**

**If exposure to internal materials within cell due to damaged outer casing,**

**LG CHEM  
PRODUCT SAFETY DATA SHEET**

**the following actions are recommended.**

**EYE CONTACT**

In case of eye contact, immediately flush eyes with plenty of water at least 15 minutes.  
Get medical attention if irritation persists or develops later.

**INHALATION**

If exposed to excessive levels of DMAc, fiber dust or fly, remove to fresh air.  
Get medical attention if cough or symptoms develop.

**SKIN CONTACT**

Wash with soap and water. Get medical attention if irritation develops or persists.  
Use hand creams to soothe and moisten irritated skin.

**INGESTION**

Not a probable route. However, in case of gastro intestinal distress following accidental ingestion, call a physician.

**SECTION 5 Fire Fighting Measures**

**FLAMMABLE PROPERTIES**

Flash point	Not applicable
Flammable limits in air	Not applicable
Lower explosive limits	Not established
Upper explosive limits	Not established
Auto-ignition temperature	Not available

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

During a fire, irritating and toxic gases and aerosols may be generated by thermal decomposition and Combustion.

**EXTINGUISHING MEDIA**

Use the following extinguishing media suitable for the materials that are burning.  
: Water, Carbon Dioxide, Dry Chemical, Foam

**FIRE FIGHTING INSTRUCTIONS**

Keep personnel removed and upwind of fire.  
Wear self-contained breathing apparatus.

**LG CHEM  
PRODUCT SAFETY DATA SHEET**

Wear full protective equipment.(full Bunker gear)

## **SECTION 6 Accidental Release Measures**

### **SAFEGUARDS(Personnel)**

Review FIRE FIGHTING MEASURES and HANDLING sections before proceeding with cleanup.  
Use appropriate personal protective equipment during cleanup.

### **SPILL CLEANUP**

Vacuum or sweep up material for salvage or disposal.

### **ACCIDENTAL RELEASE MEASURES**

Wash, shovel or mop up and place in solid waste containers.  
Do not flush to drains.

## **SECTION 7 Handling and Storage**

### **HANDLING**

Use good material handling practice.

### **STORAGE**

Store in a cool, dry place.

## **SECTION 8 Exposure Controls / Personal Protection**

### **ENGINEERING CONTROLS**

Keep away from heat and open flame.  
Good general ventilation is recommended. Local exhaust ventilation is recommended where vapors are likely to be released.

### **PERSONAL PROTECTIVE EQUIPMENT**

#### **EYE PROTECTION**

Not required beyond safety practices of employer.  
But in the event of a fire, safety glasses with side-shields for general protection are recommended.

#### **SKIN PROTECTION**

None required normal operations.  
If during a fire, wear gloves to prevent skin abrasion and irritation.

**LG CHEM  
PRODUCT SAFETY DATA SHEET**

**RESPIRATOR PROTECTION**

Respirator use must be in accordance with OSHA Standard 29 CFR 1910.134

Wear a correctly fitted, NIOSH approved, respirator or industrial type canister mask in enclosed areas with poor or no ventilation areas, or where TLV levels are likely to be exceeded.

**SECTION 9    Physical and Chemical Properties**

Form	Solid
Odor	Not applicable
PH	Not applicable
Evaporation rate	Not applicable
Vapor pressure	Not applicable
Vapor density	Not applicable
Viscosity	Not applicable
Boiling point	Not applicable
Solubility in water	Insoluble
Specific gravity	Not applicable
Density	Not applicable

**SECTION 10    Stability and Reactivity**

**CHEMICAL STABILITY**

Stable at normal temperatures and storage conditions.

**CONDITIONS TO AVOID**

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

**INCOMPATIBILITY**

None during normal operation. Avoid exposure to heat, open flame, and corrosives.

**LG CHEM  
PRODUCT SAFETY DATA SHEET**

**DECOMPOSITION**

By fire or thermal decomposition, can produce irritating and toxic gases.

**HAZARDOUS POLYMERIZATION**

Will not occur.

**SECTION 11 Toxicological Information**

**IMMEDIATE (ACUTE) EFFECTS**

None known

**DELAYED(SUBCHRONIC & CHRONIC) EFFECTS**

None known

**OTHER DATA**

Not available

**SECTION 12 Ecological Information**

No ecological information available

**SECTION 13 Disposal Considerations**

Store in impervious inert container and send to smelter for recycling. Must be treated as special waste. In general, this product may be discarded in accordance with the State and Local regulations.

**SECTION 14 Transport Information**

Lithium Ion batteries are considered to be "Rechargeable batteries" and meet the requirements of transportation by the U.S. Department of Transportation(DOT), the International Civil Aviation Administration(ICA0), the International Maritime Dangerous Goods (IMDG) Code.

Even classified as lithium ion batteries (UN3480), 2015 IATA Dangerous Goods Regulations 56th edition Packing Instruction 965 Section IB or II is applied.

The general and additional requirements apply to all lithium ion cells and batteries prepared for transport according to this packing instruction:

1) Section IB applies to lithium ion cells with a Watt-hour rating not exceeding 20 Wh and lithium ion

**LG CHEM  
PRODUCT SAFETY DATA SHEET**

batteries with a Watt-hour rating not exceeding 100 Wh packed in quantities that exceed the allowance permitted in Section II, Table 965-II; and

2) Section II applies to lithium ion cells with a Watt-hour rating not exceeding 20Wh and lithium ion batteries with a Watt-hour rating not exceeding 100 Wh packed in quantities not exceeding the allowance permitted in Section II, Table 965-II.

**TABLE 965-II**

Contents	Lithium ion cells and/or batteries with a Watt-hour rating of 2.7 Wh or less	Lithium ion cells with a Watt-hour rating of more than 2.7 Wh but not more than 20 Wh	Lithium ion batteries with a Watt-hour rating of more than 2.7 Wh but not more than 100 Wh
1	2	3	4
Maximum number of cells/batteries per package	No limit	8 cells	2 Batteries
Maximum net quantity per package	2.5 kg	N/A	N/A

Cells and/or batteries specified in columns 2, 3 and 4 of Table 965-II must not be combined in the same package.

Each cell or battery is of the type proven to meet the requirements of each test in the UN Manual of Tests and Criteria Part 3 subsection 38.3.

## **SECTION 15 Regulatory Information**

OSHA hazard communication standard (29 CFR 1910.1200)

\_\_\_\_\_Hazardous      \_\_\_\_V\_\_\_\_Non-hazardous

## **SECTION 16 Other Information**

The data in this Product Safety Data Sheet relates only to the specific product designated herein and does not relate to use in combination with any other product or in any process. This PSDS may not meet regulatory requirements in other countries. This information is based on technical information believed to be reliable. It is subject to revision as additional knowledge and experiences are gained.

### **REFERENCE**

International Chemical Safety Cards(ICSCs) International Occupational Safety and Health Information Centre(CIS) 0710 March 1999

Opinion of the scientific committee on toxicity, ecotoxicity and the environment(CSTEE)  
Adopted by the CSTEE during the 43rd plenary meeting of 28 May 2004

UN-Recommendations on the Transport of Dangerous Goods Model Regulations.  
(ST/SG/AC. 10/11 Rev.5/Amend2)