

LD1911



货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

锂电池类货物

样品名称 : ACER锂离子蓄电池/锂离子电池/锂电池(可充电)/成品配备件(锂电池组/锂离子
子电池组), AP19B8K(11.25V, 41.76Wh 3713mAh)

Sample name: ACER LITHIUM-ION BATTERY AP19B8K(11.25V, 41.76Wh 3713mAh)

委托单位 : 重庆西胜电子科技有限公司
Chongqing C-Tech Technology Co., Ltd.

生产单位 : 重庆西胜电子科技有限公司
Chongqing C-Tech Technology Co., Ltd.



Witness Better Life
SICIT 上海化工院检测有限公司
Shanghai Institute of Chemical Industry Testing Co., Ltd



货物运输条件鉴定书

NO. 212200306679614

Page 1/3

Certification for Safe Transport of Chemical Goods

样品名称 Sample Name	中文 Chinese	ACER锂离子蓄电池/锂离子电池/锂电池(可充电)/成品配备件(锂电池组/锂离子电池组), AP19B8K(11.25V, 41.76Wh 3713mAh)		
	英文 English	ACER LITHIUM-ION BATTERY AP19B8K(11.25V, 41.76Wh 3713mAh)		
委托单位 Consignor	重庆西胜电子科技有限公司 Chongqing C-Tech Technology Co., Ltd.			
生产单位 Manufacturer	重庆西胜电子科技有限公司 Chongqing C-Tech Technology Co., Ltd.			
检验方法、程序 Inspection method and procedure	国际海事组织《国际海运危险货物规则》(2020版) IMO International Maritime Dangerous Goods Code (2020 Edition)			
样品外观 Sample appearance	黑色塑胶及塑料薄膜外壳 Black Plastics cement and plastics film shell			
包装件信息 Package information	重量≤30kg。 weight≤30kg.			
序号 NO.	电池种类 Battery type	型号 Model	容量Capacity /锂含量Li content	放置方式 Placement
1	可充电锂离子电池组 Rechargeable Li-ion battery	AP19B8K	41.76Wh	电池单独运输 Battery only
鉴定结论 IDENTIFICATION CONCLUSION	1. 危险性识别(Hazards identification) 锂离子电池。 Lithium ion battery.			
	2. 海运按照国际海事组织《国际海运危险货物规则》办理的类项(Suggestion according to IMO IMDG Code) 根据特殊规定188, 该物品不受IMO IMDG Code其他条款限制。 The article is not subject to other provisions of IMO IMDG Code according to special provision 188.			
备注 Comment	3. 包装要求(Packaging requirements) 无。 None.			
	检验日期: 2021-12-14 签发日期: 2021-12-14 生效日期: 2022-01-01 Inspection Date: Issue Date: Effective Date:			



批准
Approver: 王宇

审核
Checker: 董学胜

主检
Appraiser: 强杨幸



货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

NO. 212200306679614

Page 2/3

序号 No.	检验结果及其他事项 Inspection results and other things
1	<p>本报告所述锂电池按照《国际海运危险货物规则》(2020版) 2.9.4.5规定的质量管理体系进行制造。 Lithium cells and batteries listed in this report were manufactured under the quality management program described in IMDG CODE 2020 EDITION 2.9.4.5 .</p>
2	<p>本报告所述锂电池已通过《联合国试验和标准手册》第III部分38.3小节相应测试要求。 包装件能够承受1.2m跌落试验。 Lithium cells and batteries listed in this report are of the types proved to meet the requirements of each applicable test in the UN Manual of Tests and Criteria, Part III, sub-section 38.3. The package has passed the 1.2m drop test. UN38.3试验概要编号 The UN38.3 Test Summary No. (s) 812100200830292 详细信息请扫描右侧二维码。 Please scan the QR code on the right for more information.</p> 
3	<p>锂电池完全封装在内包装内, 位于坚固的外包装中。 Lithium cells and batteries are packed in inner packagings that completely enclose the cell or battery and placed in a strong outer packaging.</p>
4	<p>电池具有适当的防短路措施。 Cells and batteries are properly protected to prevent short circuits.</p>
5	<p>每个包装件必须标示恰当的锂电池标记。 装有锂电池的包装件, 符合国际民航组织《危险物品安全航空运输技术细则》第4部分第11章的包装说明965或968第IB部分规定的, 黏贴5.2.1.10(锂电池标记)和5.2.2.2所示的9A型标签, 应视为符合本特殊规定188的规定。 Each package shall be marked with the appropriate lithium battery mark. Packages containing lithium batteries packed in conformity with the provisions of part 4, chapter 11, packing instructions 965 or 968, section IB of the ICAO Technical Instructions for the Safe Transport of Dangerous Goods by air that bear the mark as shown in 5.2.1.10(lithium battery mark) and the label shown 5.2.2.2, Model No. 9A shall be deemed to meet the provisions of this special provision 188.</p>
6	/
7	/

-验证码:402236-

货物运输条件鉴定书
Certification for Safe Transport of Chemical Goods

NO. 212200306679614
Page 3/3



acer Model Name (型号/型号): AP19B8K
(3INP5/82/70)
Rechargeable Lithium Ion Battery Pack (锂离子電池組/锂离子電池組)
(電壓/电压)Nominal voltage: 11.25V --- Typ: 3831mAh/43.08Wh
(充電限制电压)Limit charging voltage: 13.05V --- (額定容量)Rated capacity : 3713mAh/41.76Wh
 CAUTION: Risk of explosion if battery is replaced by an

有限公司
專用章
(01)

有限公司
檢驗檢測專用章
(01)

报告结束